



DIP 2x6

- 2.0*6.0, 2P 圆柱晶振
- 小型化, $\pm 10\text{ppm}$ 高精度、32.76KHZ 精准频率
- $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$ 工业级温度, 优良的耐环境特性
- 符合 RoHS、REACH 认证标准、无铅环保



规格参数 (Specifications)

Item	Specitations
频率范围 (Frequency Range)	32.768KHZ
振动模式 (Mode)	FUND
频率偏差 (Frequency Deviation)	$\pm 10\text{ppm} \sim \pm 30\text{ppm}$
频率温度特性 (Frequency Temperature Characteristics)	$-0.04\text{ppm} / (^{\circ}\text{C})$ Maximum
工作温度范围 (Operating Temperature Range)	$-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$, or specify
储存温度范围 (Storage temperature Range)	$-55^{\circ}\text{C} \sim +125^{\circ}\text{C}$
老化率 (Aging Rate)	$\pm 5\text{ppm} / \text{year}$ Maximum
负载电容 (Load Capacitance)	12.5pF, 9pF, or specify
静电容 (Static Capacitance)	2PF Maximum
激励电平 (Drive Level)	1 μw Maximum

外观尺寸 (Dimension)

