


## 3225 车规晶振

- 3.2\*2.5\*0.7mm 4P 小体积
- ±10ppm 高精度、高频率稳定性
- 滚边焊、满足无铅焊接的回流温度曲线要求
- -40°C ~ +125°C, 优良的耐环境特性
- 符合 RoHS、Reach、AEC-Q200 认证标准



## 规格参数 (Specifications)

Item	Specitations
频率范围 (Frequency Range)	8 ~ 54MHz
高阶谐波 (Overtone)	Fundamenta
频率稳定度 (Frequency Tolerance (at 25°C))	±10ppm, ±20ppm, ±50ppm or specify
工作温度范围内频率稳定度 (Frequency Stability Over Operating Temperature Range)	±50ppm Max.
工作温度范围 (Operating Temperature Range)	-40 ~ +125°C, or specify
驱动电平 (Drive Level)	100μW typical
负载电容 (Load Capacitance)	12pF, or specify
储存温度范围 (Storage temperature Range)	-40 ~ +125°C
可靠性标准 (Reliability Standard)	AEC-Q200

## 等效串联电阻 (ESR)

频率范围 (Frequency Range)	谐振电阻 (Resonance Resistance)
8 ~ 12MHz	250Ω Max.
12 ~ 20MHz	80Ω Max.
20 ~ 30MHz	60Ω Max.
30 ~ 54MHz	40Ω Max

## 外观尺寸 (Dimension)

